


AHD Full-HD Security Camera Line up

	VT-CAD01	VT-CAD02
		
Lens Type	Board Lens : 3.6mm optional 4mm/6mm/8mm	Board Lens : 3.6mm optional 4mm/6mm/8mm
	Vari-forcal:2.8~12mm optional 7~22mm	Vari-forcal:2.8~12mm optional 7~22mm
Image Chip	1/3" SONY CMOS (2.0 Mega Pixels)	1/3" SONY CMOS (2.0 Mega Pixels)
Resolution	1920(H) x 1080(V) @ 25/30fps	1920(H) x 1080(V) @ 25/30fps
Min.illumination	0.04 lux@F2.0 (AGC ON)	0.04 lux@F2.0 (AGC ON)
S/N Ratio	More than 55db	More than 55db
Coaxial Cable	3C/5C : 300 / 500 M	3C/5C : 300 / 500 M
Operating Temperature	-10°C~-50°C	-10°C~-50°C
Storage Temperature	-20°C~-70°C	-20°C~-70°C

	VT-CAT01	VT-CAT02
		
Lens Type	Board Lens : 3.6mm optional 4mm/6mm/8mm	Board Lens : 3.6mm optional 4mm/6mm/8mm
	Vari-forcal:2.8~12mm optional 7~22mm	Vari-forcal:2.8~12mm optional 7~22mm
Image Chip	1/3" SONY CMOS (2.0 Mega Pixels)	1/3" SONY CMOS (2.0 Mega Pixels)
Resolution	1920(H) x 1080(V) @ 25/30fps	1920(H) x 1080(V) @ 25/30fps
Min.illumination	0.04 lux@F2.0 (AGC ON)	0.04 lux@F2.0 (AGC ON)
S/N Ratio	More than 55db	More than 55db
Coaxial Cable	3C/5C : 300 / 500 M	3C/5C : 300 / 500 M
Operating Temperature	-10°C~+50°C	-10°C~+50°C
Storage Temperature	-20°C~+70°C	-20°C~+70°C